



Material Safety Data Sheet

Product name: ELVAX™ 360 Ethylene Vinyl Acetate Copolymer

The company encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: ELVAX™ 360 Ethylene Vinyl Acetate Copolymer

Recommended use of the chemical and restrictions on use

Identified uses: A polyethylene plastic - For industrial conversion as a raw material for manufacture of articles or goods.

Uses advised against: We recommend that you use this product in a manner consistent with the listed use. If your intended use is not consistent with the stated use, please contact your sales or technical service representative.

COMPANY IDENTIFICATION

DOW QUIMICA MEXICANA S.A. DE C.V.
AV PASEO DE LA REFORMA NO. 243
PISO 8, COLONIA CUAUHEMOC
06500 DELEGACION CUAUHEMOC CIUDAD DE MEXICO
MEXICO

Customer Information Number:

(55) 11-5184-8722
SDSQuestion@dow.com

EMERGENCY TELEPHONE NUMBER

24-Hour Emergency Contact: 01 800 369 0000

Local Emergency Contact: 01 800 369 0000

2. HAZARDS IDENTIFICATION

This product has been classified in accordance with the Globally Harmonized System of Classification and Labeling (GHS).

Hazard classification

This product is not hazardous per the Globally Harmonized System of Classification and Labelling (GHS).

Other hazards

Slipping hazard.

Dust contact with the eyes can lead to mechanical irritation.

Contact with dust can cause mechanical irritation or drying of the skin.

May form combustible dust concentrations in air.



3. COMPOSITION/INFORMATION ON INGREDIENTS

Synonyms: Ethylene copolymer

This product is a substance.

Substance name: Acetic acid ethenyl ester, polymer with ethene

CASRN: 24937-78-8

Component	CASRN	Concentration
Vinyl Acetate	108-05-4	>= 0.02 - <= 0.12 %

Note

Laboratory tests/assessments have shown that one or more components in this product is/are not bioavailable in sufficient concentrations to produce adverse effects, and therefore, do not need to be considered in the final hazard labeling of the product.

4. FIRST AID MEASURES

Description of first aid measures

General advice:

First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists refer to Section 8 for specific personal protective equipment.

Inhalation: Move person to fresh air and keep comfortable for breathing; consult a physician.

Skin contact: Seek first aid or medical attention as needed. If molten material comes in contact with the skin, do not apply ice but cool under ice water or running stream of water. DO NOT attempt to remove the material from skin. Removal could result in severe tissue damage. Seek medical attention immediately. Suitable emergency safety shower facility should be immediately available.

Eye contact: Flush eyes thoroughly with water for several minutes. Remove contact lenses after the initial 1-2 minutes and continue flushing for several additional minutes. If effects occur, consult a physician, preferably an ophthalmologist.

Ingestion: If swallowed, seek medical attention. May cause gastrointestinal blockage. Do not give laxatives. Do not induce vomiting unless directed to do so by medical personnel.

Most important symptoms and effects, both acute and delayed:

Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

Indication of any immediate medical attention and special treatment needed

Notes to physician: If burn is present, treat as any thermal burn, after decontamination. If lavage is performed, suggest endotracheal and/or esophageal control. Danger from lung aspiration must be weighed against toxicity when considering emptying the stomach. No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.



5. FIREFIGHTING MEASURES

Extinguishing media

Suitable extinguishing media: Water spray. Alcohol-resistant foam. Carbon dioxide (CO₂). Dry chemical.

Extinguishing Media to Avoid: None known..

Special hazards arising from the substance or mixture

Hazardous combustion products: Carbon oxides.

Unusual Fire and Explosion Hazards: Exposure to combustion products may be a hazard to health.. Pneumatic conveying and other mechanical handling operations can generate combustible dust. To reduce the potential for dust explosions, do not permit dust to accumulate.. Product can accumulate electrostatic charges. Static discharge in the presence of volatile or flammable mixtures presents a potential fire or explosion hazard.. May form combustible dust concentrations in air (during processing).. Molten polyethylene tends to flow or drip and will propagate fire..

Advice for firefighters

Fire Fighting Procedures: Use water spray to cool unopened containers.. Evacuate area.. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.. If material is molten, do not apply direct waterstream. Use fine water spray or foam..

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Remove undamaged containers from fire area if it is safe to do so.

Special protective equipment for firefighters: Wear self-contained breathing apparatus for firefighting if necessary.. Use personal protective equipment..

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures: Spilled material may cause a slipping hazard. Follow safe handling advice and personal protective equipment recommendations.

Removal of ignition sources: Keep away from sources of ignition.

Dust Control: Use care to minimize generation of airborne dust.

Environmental precautions: Discharge into the environment must be avoided. Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up: Sweep up or vacuum up spillage and collect in suitable container for disposal. Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration. Local or national regulations may apply to releases and disposal of this material, as well as those materials and



items employed in the cleanup of releases. You will need to determine which regulations are applicable.

See sections: 7, 8, 11, 12 and 13.

7. HANDLING AND STORAGE

Precautions for safe handling: Avoid breathing process fumes. Do not breathe dust. Minimize dust generation and accumulation. Keep container closed when not in use. Keep away from heat and sources of ignition. Take precautionary measures against static discharges. Use with adequate ventilation. Take care to prevent spills, waste and minimize release to the environment. Pneumatic conveying and other mechanical handling operations can generate combustible dust. To reduce the potential for dust explosions, do not permit dust to accumulate. Do not get molten material in eyes, on skin or clothing. Handle in accordance with good industrial hygiene and safety practice.

CONTAINERS MAY BE HAZARDOUS WHEN EMPTY. Since emptied containers retain product residue follow all (M)SDS and label warnings even after container is emptied.

Use only with adequate ventilation. This material can accumulate static charge due to its inherent physical properties and can therefore cause an electrical ignition source to vapors. In order to prevent a fire hazard, as bonding and grounding may be insufficient to remove static electricity, it is necessary to provide an inert gas purge before beginning transfer operations. Static electricity may accumulate and ignite suspended dust causing an explosion. Provide adequate precautions, such as electrical grounding and bonding, or inert atmospheres.

Conditions for safe storage: Keep in properly labelled containers. Store in accordance with the particular national regulations.

Do not store with the following product types: Strong oxidizing agents.

Unsuitable materials for containers: None known.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

If exposure limits exist, they are listed below. If no exposure limits are displayed, then no values are applicable.

Although some of the components of this product may have exposure guidelines, no exposure would be expected under normal handling conditions due to the physical state of the material.

Exposure controls

Engineering controls: Provide general and/or local exhaust ventilation to control airborne levels below the exposure guidelines. Local exhaust ventilation is preferred for most operations.

Individual protection measures

Eye/face protection: Use safety glasses (with side shields). If there is a potential for exposure to particles which could cause eye discomfort, wear chemical goggles. If exposure causes eye discomfort, use a full-face respirator.

Skin protection

Hand protection: Chemical protective gloves should not be needed when handling this material. Consistent with general hygienic practice for any material, skin contact should be minimized. Use gloves to protect from mechanical injury. Selection of gloves will depend on the task. Use gloves with insulation for thermal protection, when needed.



Other protection: No precautions other than clean body-covering clothing should be needed.

Respiratory protection: Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process. Use an approved air-purifying respirator when vapors are generated at increased temperatures or when dust or mist is present.

The following should be effective types of air-purifying respirators: When dust/mist are present use a/an Particulate filter. When combinations of vapors, acids, or dusts/mists are present use a/an Organic vapor cartridge with a particulate pre-filter.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	
Physical state	pellets
Color	clear
Odor	ester-like
Odor Threshold	No data available
pH	Not applicable
Melting point/range	78 °C
Freezing point	No data available
Boiling point (760 mmHg)	Not applicable
Flash point	open cup 260 °C <i>Cleveland open cup - COC</i>
Evaporation Rate (Butyl Acetate = 1)	Not applicable
Flammability (solid, gas)	May form combustible dust concentrations in air during processing, handling or other means.
Lower explosion limit	Not applicable
Upper explosion limit	Not applicable
Vapor Pressure	Not applicable
Relative Vapor Density (air = 1)	Not applicable
Relative Density (water = 1)	0.948
Water solubility	negligible
Partition coefficient: n-octanol/water	No data available
Auto-ignition temperature	No data available
Decomposition temperature	>230 °C Decomposition can occur with extended residence time in the extruder.
Dynamic Viscosity	Not applicable
Kinematic Viscosity	Not applicable
Explosive properties	No data available
Oxidizing properties	The substance or mixture is not classified as oxidizing.
Molecular weight	No data available



NOTE: The physical data presented above are typical values and should not be construed as a specification.

10. STABILITY AND REACTIVITY

Reactivity: Not classified as a reactivity hazard.

Chemical stability: Stable under normal conditions.

Possibility of hazardous reactions: Dust can form an explosive mixture in air.

Conditions to avoid: None known.

Incompatible materials: Incompatible with strong bases and oxidizing agents.

Hazardous decomposition products:

Decomposition products can include and are not limited to: Carbon monoxide. Hydrocarbons. Organic acids. Aldehydes. Acrolein. Alcohols. Ketones.

11. TOXICOLOGICAL INFORMATION

Toxicological information appears in this section when such data is available.

Information on likely routes of exposure

Eye contact, Skin contact, Ingestion.

Acute toxicity (represents short term exposures with immediate effects - no chronic/delayed effects known unless otherwise noted)

Acute oral toxicity

Very low toxicity if swallowed. Harmful effects not anticipated from swallowing small amounts. May cause choking if swallowed.

Single dose oral LD50 has not been determined.

Typical for this family of materials.
LD50, Rat, > 5,000 mg/kg Estimated.

Information for components:

Vinyl Acetate

LD50, Rat, 2,500 - 3,000 mg/kg Estimated.

Acute dermal toxicity

No adverse effects anticipated by skin absorption.

The dermal LD50 has not been determined.

Typical for this family of materials.
LD50, Rabbit, > 2,000 mg/kg Estimated.

**Information for components:****Vinyl Acetate**

LD50, Rabbit, male, 7,440 mg/kg

Acute inhalation toxicity

No adverse effects are anticipated from single exposure to dust. Vapors released during thermal processing may cause respiratory irritation.

The LC50 has not been determined.,

Information for components:**Vinyl Acetate**

Vapor concentrations are attainable which could be hazardous on single exposure. Vapor may cause irritation of the upper respiratory tract (nose and throat).

LC50, Rat, 4 Hour, vapour, 14.084 - 15.810 mg/l

Skin corrosion/irritation

Typical for this family of materials.

Prolonged contact is essentially nonirritating to skin.

Mechanical injury only.

Under normal processing conditions, material is heated to elevated temperatures; contact with the material may cause thermal burns.

Information for components:**Vinyl Acetate**

Brief contact is essentially nonirritating to skin.

Prolonged contact may cause severe skin irritation with local redness and discomfort.

May cause rash or blisters.

Serious eye damage/eye irritation

Typical for this family of materials.

Solid or dust may cause irritation or corneal injury due to mechanical action.

Elevated temperatures may generate vapor levels sufficient to cause eye irritation. Effects may include discomfort and redness.

Information for components:**Vinyl Acetate**

May cause slight eye irritation.

May cause slight corneal injury.

Vapor may cause eye irritation experienced as mild discomfort and redness.

Sensitization

For skin sensitization:

No relevant data found.

For respiratory sensitization:

No relevant data found.

Information for components:

**Vinyl Acetate**

Skin contact may cause an allergic skin reaction in a small proportion of individuals. Did not demonstrate the potential for contact allergy in mice.

For respiratory sensitization:
No relevant data found.

Specific Target Organ Systemic Toxicity (Single Exposure)

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

Information for components:**Vinyl Acetate**

May cause respiratory irritation.

Route of Exposure: Inhalation

Target Organs: Respiratory Tract

Due to the physical state of the material, this component is not expected to be bioavailable under normal handling and processing conditions.

Aspiration Hazard

Based on physical properties, not likely to be an aspiration hazard.

Information for components:**Vinyl Acetate**

Based on available information, aspiration hazard could not be determined.

Chronic toxicity (represents longer term exposures with repeated dose resulting in chronic/delayed effects - no immediate effects known unless otherwise noted)**Specific Target Organ Systemic Toxicity (Repeated Exposure)**

No relevant data found.

Information for components:**Vinyl Acetate**

In animals, effects have been reported on the following organs:

Lung.

Respiratory tract.

Due to the physical state of the material, this component is not expected to be bioavailable under normal handling and processing conditions.

Carcinogenicity

Contains a component(s) that is/are not expected to be bioavailable due to the physical state of the material under normal handling and processing conditions.

Information for components:**Vinyl Acetate**

Vinyl acetate has caused cancer in some laboratory animals exposed to high vapor levels in long-term studies; tumors and other respiratory tract lesions occurred secondarily to chronic irritation. Vinyl acetate has caused tumors of the gastrointestinal tract in a drinking water study. Tumors occurred only at high doses, and mechanistic studies indicate that they



occurred secondarily to irritation. Due to the physical state of the material, this component is not expected to be bioavailable under normal handling and processing conditions.

Teratogenicity

No relevant data found.

Information for components:**Vinyl Acetate**

Did not cause birth defects or any other fetal effects in laboratory animals.

Reproductive toxicity

No relevant data found.

Information for components:**Vinyl Acetate**

In animal studies, did not interfere with reproduction.

Mutagenicity

No relevant data found.

Information for components:**Vinyl Acetate**

In vitro genetic toxicity studies were negative in some cases and positive in other cases. Animal genetic toxicity studies were negative.

12. ECOLOGICAL INFORMATION

Ecotoxicological information appears in this section when such data is available.

General Information

No data is available on the product itself. Toxicity is expected to be low based on insolubility in water.

Toxicity**Acute toxicity to fish**

Not expected to be acutely toxic, but material in pellet or bead form may mechanically cause adverse effects if ingested by waterfowl or aquatic life.

Persistence and degradability

Biodegradability: This water-insoluble polymeric solid is expected to be inert in the environment. Surface photodegradation is expected with exposure to sunlight. No appreciable biodegradation is expected.

Bioaccumulative potential

Bioaccumulation: No bioconcentration is expected because of the relatively high molecular weight (MW greater than 1000).

Mobility in soil

In the terrestrial environment, material is expected to remain in the soil.
In the aquatic environment, material is expected to float.

**Results of PBT and vPvB assessment**

This substance has not been assessed for persistence, bioaccumulation and toxicity (PBT).

Other adverse effects

No relevant data found.

13. DISPOSAL CONSIDERATIONS

Disposal methods: DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. AS YOUR SUPPLIER, WE HAVE NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN MSDS SECTION: Composition Information. FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: Recycler. Reclaimer. Incinerator or other thermal destruction device. Landfill.

Treatment and disposal methods of used packaging: Empty containers should be recycled or otherwise disposed of by an approved waste management facility. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. Do not re-use containers for any purpose.

14. TRANSPORT INFORMATION

Classification for ROAD and Rail transport:

Not regulated for transport

Classification for SEA transport (IMO-IMDG):

Not regulated for transport

**Transport in bulk
according to Annex I or II
of MARPOL 73/78 and the
IBC or IGC Code**

Consult IMO regulations before transporting ocean bulk

Classification for AIR transport (IATA/ICAO):

Not regulated for transport

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.



15. REGULATORY INFORMATION

It is recommended the customer to check in the location of use of this product whether it is specifically regulated for human perusal or veterinary applications, as food and pharmaceuticals additives or packaging, domissanitary, and cosmetics, or even as controlled agent recognized as precursor to drug, chemical weapons, and ammunition manufacture.

The communication of the hazards of this product is in accordance with local and international legislations, observing always the most restrictive requirement.

16. OTHER INFORMATION

Other information

Refer to NFPA 654, Standard for the Prevention of Fire and Dust Explosions from the Manufacturing, Processing, and Handling of Combustible Particulate Solids, for safe handling.

Revision

Identification Number: 89002917 / A233 / Issue Date: 19.04.2021 / Version: 2.0

Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

Full text of other abbreviations

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECS - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations;



UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Information Source and References

This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references within our company.

The information is considered as correct, but not exhaustive, and will be used only as a guide, which is based in the current knowledge of the substance or mixture, and is applicable to proper safety precautions for the product.

DOW QUIMICA MEXICANA S.A. DE C.V. urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.

MX